

SPECIFIC TOOL KIT FOR HFF 134

DETAIL OF CONTENTS

Quantity	Description	Photo
1	Portable thermometer delivered including: -a digital display box with the possibility of connecting two probes -a battery for the case -two wired probes of thermocouple type -a thermocouple type contact probe	
1	Recovery station type MINIMAX E: -light machine, equipped with an oil-free compressor -Liquid phase 90 kg/h -Vapour phase 9 kg/h -Push-pull 354 kg/h -equipped with two pressure gauges (LP and HP) -HP pressure switch -compatible fluids A2L	
1	Electronic refrigerant leakage detector -Tricolor visual indicator of the leak to 6 segments for 18 alarm levels -Sensitivity 3g/year, 7 levels. -Power supply per battery.	
1	vacuum pump REFAIRCO PK-25-SV: -Flow rate: 70L/min -See final 0.02mbar -Compatible A2L fluids -Fitting 1/4 SAE -50mm diam vacuumeter and solenoid valve -Weight 7kgs	
1	Manifold with dry pressure gauges -manifold 2 ways for R22 / R134a / R404A / R407C -High quality aluminum body with LED -Piston valves and PTFE seals -Dry "pulse-free" pressure gauges -Metal body with adjustment screws -Comes with sturdy case and hoses	
1	Electronic scale -Capacity: 0 to 100 kg -resolution : 10grs -size of the plate : 230x230mm	

Recommended equipment

- REFRIGERANT TRANSFER TRAINER

- Ref : HFF 134